Weapons Clearing Procedures Cards

Marines, cut these out and keep them with you. Use them to remind yourself of the right thing to do.

WEAPONS CLEARING PROCEDURES

M16-series and M4 Rifles M9 PISTOL

Fointeeappe into clearing barrel for all steps. 1. Place the weapon on "safe".

- Remove the magazine from the rifle.
- Lock the bolt/blide to the rear.
- Visually inspect the chamber/remove any ammunition.
- Let the bolt/slide go forward.
- 6. Place the weapon on "fire".
- 7. Pull the trigger.

For Mt6-series Rifles:

- Charge the weapon.
- 9. Place the weapon on "safe".

- Place the weapon "safe".
- Return weapon to holater.



M249 Squad Automatic Weapon

from spon into it string but in for all street. Race the weapon on "fire".

- Lock the boilt to the rew

- Return and lock the colling handle to the forward position.
 Race the weapon on "safe".
 Raise the ower and feed mechanism assembly and conduct \$-point. ammo check:
 - Checkfeed panil assembly under the feed cover.
 Direck the feed tray assembly.
 Lift feed tray assembly and check the chamber.

 - d. Check the space between the bolt ascendily and the chandler.
 e. Insert 2 fingers of left hand into magazine well to extract anmo.
 Close the cover and feed mechanism.
- flace the weapon on "fire".
- Return the cooking handle to the rear position.
- 9. Pull the trigger, ease the bolt forward.



M240G Machine Gun

- Emission with a well for a see.

 1. Floo the vespon on "fire".

 2. Leas the seepon on "fire".

 3. Return the cooking lever to the toround position.

 4. Floo the vespon on "sele".

 5. Flore the vespon on "sele".

 6. Flore the fire over as embly and conduct 4-point check for an mo:

 a. Check the fired tray;

 6. Check the fired tray;

 6. Unit to fired the fired tray;

 6. Unit to fired the fired tray;

 6. One tray;

 6. O
- d. Clinick between the face of the bottand the chamber (including under the bott and operating rod a re-inter).

 4. Co is the feed that and cover a re-inter;

 7. Root the interport on "the".

 E. Pull the coving rend of the rear and hold if.

- Pull the trigger, ease the boilt forcerd.



WEAPONS CLEARING PROCEDURES

M203 Grenade Launcher

- 1. Point Weapon in a safe direction.
- Put Wespon on safe.
- Push in the release button, and pull the barrel forward.
- 4. Watch to see if a round extracts. Catch round, don't let it
- inspect the breach to ensure a round is not present.
- 7. Pull the barrel to the rear until it dicks. This cooks the
- 8. Put the Wespon on safe.



MK 19 Automatic Grenade Launcher

- 1. Placethe weapon on SAFE.
- 2. Open the cover assembly.
- Lover one charger handle.
- 4. Pull the charger handle slightly to the rear, allowing sufficient space between the face of the bolt and the chamber to see both. Check for live ammunition.
- Ride the bolt forward.
- 8. Return the charger handle to its original upright position.



M2 50 CAL Machine Gun

- Place safety on "\$" (safe) (M40 turnet type and fixed type).
- Unlock the bolt latch release.
- Raise the cover.
- 4. Lift the cartridge extractor and remove the ammunition belt from the feed way
- 5. Place cartridge extractor down and close the cover
- 6. Pull and lock the bolt to the rear, leaving the retracting slide handle to the rear. Open the cover.
- 7. NOTE: Step 7 is for the MIS turnet type and fixed type. Move M 10 lock selector to the rear. Charge the weapon.

 8. Visually inspect the chamber and T-slot for rounds (in
- Darkness the gunner must feel the chamber and T-slot to ensure they are clear).
- 9. Press the bolt latch release and ease the bolt forward with retracting slide handle.
- 10. Move the M10 lock selector forward and pull back on the charging handle until a click is heard, then ease the bolt forward.
- 11. Close the cover.
- 12. Place the safety on "F" fire.
- 13. Press the trigger.

